

FLIFT		CXD10/15 order picker (Man Mount)			
Model		CXD10-45	CXD10-60	CXD10-60	CXD15-60
Rated Capacity	kg	1000	1000	1000	1500
Load Center	mm	450	450	450	450
Dynamic Type		Fully Electric	Fully Electric	Fully Electric	Fully Electric
Operation Type		Man Mount	Man Mount	Man Mount	Man Mount
Overall weight	kg	2600	2900	2650	3150
Driving Wheel	mm	230*75	230*75	230*75	230*75
Front wheel	mm	150*90	150*90	150*90	150*90
Auxiliary Wheel		130*55	130*55	130*55	130*55
Lifting Height	mm	4260	5760	6000	6000
MAX. Fork lifting height	mm	4860	6360	6000	6000
Overall Length	mm	2830	2830	2720	3065
Overall Width	mm	1160	1160	1160	1342
Mast Lowered Height	mm	2310	2820	2885	2885
Mast Extended Height (with backrest)	mm	6510	8010	8250	8250
Overhead Guard Height	mm	2250	2250	2250	2250
Min. Ground Clearance	mm	50	50	50	50
Min. height of operating table from ground	mm	240	240	240	240
Auxiliary lifting height	mm	600 (optional)	600 (optional)	0	0
Max. height of operating table from ground	mm	4500	6000	6240	6240
Fork Size	mm	920*100*40	920*100*40	920*100*40	920*100*40
Fork outside width	mm	680	680	680	680
Turning Radius	mm	1735	1735	1635	1635
Right-angle channel (1200 horizontal x1000)		3285	3285	3180	3180
Driving Speed (full/no load)	km/h	4km/h/5km/h	4km/h/5km/h	4km/h/5km/h	4km/h/5km/h
Gradeability	%	0	0	0	0
Braking mode		Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
Driving motor	V/KW	24/1.6	24/1.6	24/2.2	24/2.2
Lifting motor	V/KW	24/3.0	24/3.0	24/3.0	24/3.0
Storage Battery	V/Ah	24/360	24/360	24/420	24/420
Lifting Speed (full/no load)	mm/s	115/100	115/100	115/100	115/100
Descend Speed(full/no load)	mm/s	125/200	125/200	125/200	125/230