



BOPP Film Reel Stacker Specifications

Model		CDD10D-13
Power type		Electric
Operation mode		Walkie Type
Rated load	kg	1000
Load center distance	mm	500
Tire type Front/rear		Polyurethane
Load wheel		Φ85*70
Drive wheel		φ250*80
Auxiliary wheel		Φ130*55
Mast type		(Customized Single Column Mast)
Standard lifting height	mm	1300
Maximum Ground Clearance	mm	25
Arc-shaped Pallet Holder width	mm	1100
Arc-shaped Pallet Holder Tilt Angle	°	3 / 5 (F/ R)
Overall length	mm	1750
Overall width	mm	1100
Mast lowered height	mm	1850
Aisle width (Min.Right Angle Stacking Aisle Width)	mm	2100
Turning radius	mm	1650
Travel speed(Full load/no load)	km/h	3.5 / 4
Lifting speed (Full load/no load)	mm/s	85/125
Descending speed (Full load/no load)	mm/s	155/105
Climbing gradeability(Full load/no load)	%	6°/ 10°
Drive motor power	kw	1.5
Lifting motor power	kw	2.2
Battery Voltage/capacity	V/Ah	24/210
Battery Type		Lead - Acid
Service Weight(including battery)	Kg	Around 750
Steering type		Mechanical steering
Parking brake type		Electromagnetic brake
Parking brake operation mode		Handle operation

Notice:

Due to this machinery is belong to the individually customized product.
So the final confirmed production drawing will be little differences from the above specifications,
or superior to above specifications.

